

THE DETAIL GIVEN BELOW OFFERS A GUIDE IN PRINCIPLE ONLY AND SHOULD BE CHECKED WITH THE MANUFACTURERS OF THE RELEVANT COMPONENT FOR ACCURACY BEFORE INSTALLATION

8mm Thick Rockpanel Rockclad Durable with Protect Plus Finish.

EPDM Gasket.

Vertically fixed timber batten. Minimum thickness of 28mm

Breathable membrane.

Insulation board.

Panels fixed with Torx headed screws in accordance with Rockpanel specification.

Horizontally laid timber batten.

Cement Particle Board.

Plasterboard with internal paint finish.

Vertically fixed Timber battens.

Polythene Vapour Control Layer.

Lightweight Steel Frame.

±28\*

\* FOR ROCKPANEL SYSTEMS REQUIRING NHBC APPROVAL A CAVITY DEPTH OF 35mm IS REQUIRED.

**DETAIL 11 - ROCKCLAD DURABLE WITH PROTECT PLUS FINISH  
VERTICAL SECTION TIMBER SUBSTRUCTURE TO STRUCTURAL CONCRETE WITH LIGHT STEEL FRAME.**



BREEAM is a registered trademark of BRE (the Building Research Establishment Ltd. Community Trade Mark E5778551).  
The BREEAM marks, logos and symbols are the Copyright of BRE and are reproduced by permission.  
Green Guide Element numbers A+ rated: 1006260002 / 1006270005 / 1006280007 / 1006210008 / 1006260010 / 1006270013 / 1006280015 / 1006210016  
Green Guide Element numbers with A rated: 1006230001 / 1006260003 / 1006240004 / 1006250006 / 1006230009 / 1006260011 / 1006240012 / 1006250014